

**Head Office**

2nd Floor Helvetia House
Greenvale Road
Wilbart, Germiston
PO Box 4455, Edenvale 1610
Tel: 010 593 2717
Fax: 011 450 3125
www.cpw.co.za

Wynberg

766 5th Street,
Wynberg, Johannesburg
Tel: 010 593 2717

Alrode

5 Vereeniging Road,
Alrode, Johannesburg
Tel: 010 593 2717

Cape Town

Unit 14, 44 Paarden Eiland Road
Paarden Eiland, Cape Town
Tel: 010 593 2717

Montana

371 Calliandra Street,
Montana, Pretoria
Tel: 010 593 2717

Centurion

130 Edward Street,
Centurion, Pretoria
Tel: 010 593 2717

Strijdom Park

130 Edward Street,
Centurion, Pretoria
Tel: 010 593 2717

Bloemfontein

2 Enterprise Street
Hamilton, Bloemfontein
Tel: 010 593 2717

CPW JOINTING PLASTER DATA SHEET

CPW – Ceiling and Partition Warehouse is a company that prides itself on superior quality products and customer service. Our jointing plaster is manufactured to high quality standards to ensure that all plasterboard jointing requirements are met.

CPW Jointing Plaster is a powder compound used for finishing the joints between plasterboards in drywall and ceiling applications, thereby creating a smooth and uniform surface. Fibre jointing tape is to be applied over the joints before the jointing plaster is applied. CPW Jointing Plaster is made from natural gypsum and a nominal amount of additives ensuring smooth mixing and workability and ease of application.

PHYSICAL PROPERTIES:

Appearance:	Fine white powder, odourless
Packaging:	20Kg Bags
Coverage per 20kg:	Approximately 35 linear metres
Water / Plaster Ratio:	6 – 6.5lt clean water to 10kg Jointing Plaster
Workability:	Approximately 60 minutes
Final setting time:	Approximately 120 minutes
Composition:	Calcium Sulphate Hemihydrate, silica's, accelerant and retarder.
Combustibility:	Non Combustible

HEALTH AND SAFETY INFORMATION:

CPW Jointing Plaster is classified as non-hazardous

Health Effects and First Aid Measures:

- If Swallowed: Although unlikely under normal conditions of use, ingestion of this product may be harmful and may lead to abdominal discomfort. Wash mouth out with clean water and drink copious amounts of water, seek medical advice.
- Eye Contact: May result in eye irritation, itching, eye watering and inflammation. Flush eyes with plenty of water, seek medical advice if symptoms persist.
- Skin Contact: Exposure over a long period may cause skin dryness and irritation. Wash skin with a mild soap and clean water, apply a scent free skin lotion.
- Inhalation: Excessive inhalation of this product may result in respiratory irritation including coughing and sneezing. Seek fresh air should inhalation of this product occur. Seek medical attention if symptoms persist.

No long term health effects have been reported

Recommended Precautions:

- Avoid generating dust in poorly ventilated areas
- Use a respirator or dust mask if excessive dust is generated
- Safety goggles are to be worn to protect the eyes from dust irritation
- Should the product cause skin irritation, wear suitable gloves
- Particular precaution should be taken when product is to be sanded

Disposal Considerations:

Use an authorized landfill site in accordance with current Waste Management Licensing Regulations for disposal.

Accidental Release Measures:

Vacuum or sweep up excess compound and transfer to a suitable container to control dust formation and to prevent these products from contaminating drains, watercourses, ground or soil. Do not hose into drains as blockages may occur.

Handling and Storage:

Care should be taken when lifting single bags of jointing plaster by hand to ensure that back injuries do not occur. Pallets of jointing plaster are to be moved by mechanical handling equipment only.

CPW Jointing Plaster is to be stored in a dry and protected area. Bags of plaster are to be stored off of the ground on suitable supports or pallets. Moisture is to be avoided. Open bags that still contain product are to be sealed tightly to avoid dust spreading and to protect the product. Use the product within one year after production. Product should be stored and used in a minimum temperature of 5°C and a maximum temperature of 40°C.