



CPW VINYL TILES DATA SHEET

CPW – Ceiling and Partition Warehouse is a company that prides itself on superior quality products and customer service. Our ceiling tile range is no exception with easy to clean vinyl covering; neat, taped edges and foil backing to ensure that all your ceiling requirements are met.

Specification:

Dimensions: 1200X600 (+0, -5)
Thickness: 9mm
Facing: Fissured or White Vinyl
Edges: Taped
Backing: Foil
Weight: Approximately 7kg/m²
Squareness: Maximum 2mm Difference
Appearance: Surface clean, no delamination, grooves or bubbles
Position: Vinyl to be a maximum of 2mm from edge of board
Edges: No broken corners

Composition:

Calcium Sulphate Dihydrate (gypsum) encased within paper liners and additional nominal amounts of additives. Aluminium foil backed, vinyl laminated to face and plastic tape around the edges.

Hazards:

These products are defined as non-hazardous.

Supporting Structure:

- To ensure a high quality of finish, it is essential that the supporting structure is accurate and sound.
- Additional supports are required at positions of light fittings.
- Air conditioners/ventilating equipment must not be supported from ceiling grid and must have their own independent support.

Advantages:

Light in mass – 7kgs/m ² (nominal)	Easy to handle
Quick to cut	Easy to clean

The foil backing of CPW Vinyl Ceiling Tiles provides an effective vapour barrier and is moisture resistant to small amounts of water (such as condensation from air conditioning). Foil backing also improves thermal resistance by acting in a heat reflecting manner and improves NRC properties.

The taped edges of the CPW Vinyl Ceiling Tile increase the life span of the tile, reduces gypsum dust and increases water resistance.

Handling and storage:

Care should be taken to ensure that the CPW Vinyl ceiling tiles are not dropped or subjected to rough handling. Vinyl ceiling tiles should be stored in a dry area. The stacks must be packed on suitable timber supports, maximum 400mm apart and off the ground. A level, clean and dry storage area must be made available.

Special care should be taken to ensure that the vinyl finish is not soiled or damaged during handling.

Tiles can be cleaned of dust marks with a mild detergent if necessary.

Head Office

2nd Floor Helvetia House
Greenvale Road
Wilbart, Germiston
PO Box 4455, Edenvale 1610
Tel: 010 593 2717
Fax: 011 450 3125
www.cpw.co.za

Wynberg

766 5th Street,
Wynberg, Johannesburg
Tel: 010 593 2717

Alrode

5 Vereeniging Road,
Alrode, Johannesburg
Tel: 010 593 2717

Cape Town

Unit 14, 44 Paarden Eiland Road
Paarden Eiland, Cape Town
Tel: 010 593 2717

Montana

371 Calliandra Street,
Montana, Pretoria
Tel: 010 593 2717

Centurion

130 Edward Street,
Centurion, Pretoria
Tel: 010 593 2717

Strijdom Park

130 Edward Street,
Centurion, Pretoria
Tel: 010 593 2717

Bloemfontein

2 Enterprise Street
Hamilton, Bloemfontein
Tel: 010 593 2717