

## CPW VINYL TILES DATA SHEET

CPW – Ceiling and Partition Warehouse is a company that prides itself on superior quality products and customer service. Our ceiling tile range is no exception with easy to clean vinyl covering; neat, taped edges and foil backing to ensure that all your ceiling requirements are met.

### Specification:

Dimensions:	1200X600 (+0, -5)
Thickness:	9mm & 12.5mm
Facing:	Fissured or White Vinyl
Edges:	Taped
Backing:	Foil
Weight:	Approximately 5kg/m <sup>2</sup> and 7kg/m <sup>2</sup> respectively
Squareness:	Maximum 2mm Difference
Appearance:	Surface clean, no delamination, grooves or bubbles
Position:	Vinyl to be a maximum of 2mm from edge of board
Edges:	No broken corners

### Composition:

Calcium Sulphate Dihydrate (gypsum) encased within paper liners and additional nominal amounts of additives. Aluminium foil backed, vinyl laminated to face and plastic tape around the edges.

Hazards: These products are defined as non-hazardous.

### Supporting Structure:

- To ensure a high quality of finish, it is essential that the supporting structure is accurate and sound.
- Additional supports are required at positions of light fittings.
- Air conditioners/ventilating equipment must not be supported from ceiling grid and must have their own independent support.

The foil backing of CPW Vinyl Ceiling Tiles provides an effective vapour barrier and is moisture resistant to small amounts of water (such as condensation from air conditioning). Foil backing also improves thermal resistance by acting in a heat reflecting manner and improves NRC properties. The taped edges of the CPW Vinyl Ceiling Tile increase the life span of the tile, reduces gypsum dust and increases water resistance.

### Handling and storage:

Care should be taken to ensure that the CPW Vinyl ceiling tiles are not dropped or subjected to rough handling. Vinyl ceiling tiles should be stored in a dry area. The stacks must be packed on suitable timber supports, maximum 400mm apart and off the ground. A level, clean and dry storage area must be made available.

Special care should be taken to ensure that the vinyl finish is not soiled or damaged during handling. Tiles can be cleaned of dust marks with a mild detergent if necessary.

<b>HEAD OFFICE</b> 75 Linksfield Rd. Dowerglen Edenvale	<b>CENTRAL DISTRIBUTION</b> 5 Vereeniging Road Alrode Alberton	<b>CPW DISTRIBUTION BEE LEVEL2</b> 5 Vereeniging Road Alrode Alberton	<b>BLOEMFONTEIN</b> 5 Church Street Hamilton Bloemfontein
<b>WYNBERG</b> 9 Chadwick Avenue Wynberg Johannesburg	<b>MONTANA</b> 371 Calliandra Street Montana Pretoria	<b>STRIJDOM PARK</b> 12 Remblok Street Strijdom Park Ex12 Randburg	<b>CAPE TOWN</b> 56 Auckland Street Paarden Eiland Cape Town

 010 601 6128

 [www.cpw.co.za](http://www.cpw.co.za)

HEAD OFFICE  
75 Linksfield Rd.  
Dowerglen  
Edenvale

CENTRAL DISTRIBUTION  
5 Vereeniging Road  
Alrode  
Alberton

CPW DISTRIBUTION  
BEE LEVEL2  
5 Vereeniging Road  
Alrode  
Alberton

BLOEMFONTEIN  
5 Church Street  
Hamilton  
Bloemfontein

WYNBERG  
9 Chadwick Avenue  
Wynberg  
Johannesburg

MONTANA  
371 Calliandra Street  
Montana  
Pretoria

STRIJDOM PARK  
12 Remblok Street  
Strijdom Park Ex12  
Randburg

CAPE TOWN  
56 Auckland Street  
Paarden Eiland  
Cape Town



010 601 6128



[www.cpw.co.za](http://www.cpw.co.za)